



Data sheet 50C2.75-53



50C2.75-53

CWL: Continuous running water level
LWL: Lowest running water level



Specification

Elektrische Tauchpumpe C-Serie
Degree of protection IP 68
Pressure resistance max. 15 m
Type of impeller single channel impeller
Free passage 21 mm
Suitable for:
sewage water and liquids carrying solids

Electric motor

Dry-type submersible induction motor
Insulation class E 2Poles 2810 1/min
Starting mode Direct starting
Rated voltage 400 V 50 Hz 3~
Power uptake 1,13 kW
Rated power 0,75 kW
Rated current 1,9 A
Start current 8,5 A

Cable

10m H07RN-F 4Cx1,5mm²

Motor Protection

Miniature protector in windings
(snap-action bi-metal device)

Shaft seal

Double inside mechanical seal in oil bath
additional lubrication by oil lifting device
Primary seal
Silicon carbide on silicon carbide
Secondary seal
Silicon carbide on silicon carbide

Bearings

Shielded ball bearings, maintenance-free

Materials

Impeller
FC20 (EN-GJL-200) + Tungsten carbide
Pump casing FC200 (EN-GJL-200)
Suction cover FCD700 (EN-GJS-700-2)
Motor Frame FC200 (EN-GJL-200)
Shaft SUS403 (EN-X6Cr13)

Discharge size

2" DIN-Flansch / JIS 10K-Flansch
guide rail fitting optional


Weight

24 kg (dry weight of the pump only without cable)

Performance curve



50C2.75-53

Discharge port	2"
FördH	11,5 m
Flow	20,0 m³/h
Rated power	0,75 kW
Power input	1,13 kW
Phases	3~
Voltages	400 V
Frequency	50 Hz
Rated current	1,9 A
Starting current	8,49 A
Number of poles	2
Speed	2810 1/min
Starting mode	Direct starting
Insulation class	E



Dimensions


50C2.75-53



50C2.75-53

CWL: Continuous running water level
LWL: Lowest running water level

Sectional drawing 50C2.75-53



No.	Description	Remark	No.	Description	Remark
1	Cable	H07RN-F	54	Shaft	SUS403 (EN-X6Cr13)
20	Pump casing	FC200 (EN-GJL-200)	55	Rotor	.
21	Impeller	FC20 (EN-GJL-200) + Tungsten carbide	56	O--	.
22	Suction cover	FCD700 (EN-GJS-700-2)	60	Bearing Housing	FC200 (EN-GJL-200)
23	Stand support	FCD45 (EN-GJS-450-10)	64	Motor Frame	FC200 (EN-GJL-200)
25	Mechanical seal	H-20A	72	Eye screw	SUS304 (EN-X5CrNi18-10)
26	Oil seal	TC32488			
30	Oil distributor	Plastic			
35	Oil screw	SUS304 (EN-X5CrNi18-10)			
36	Lubricant	Turbine oil (ISO VG32)			
37	Discharge bend	FC200 (EN-GJL-200)			
46	Air vent screw	Nylon			
48	Screwed Flange	FC200 (EN-GJL-200)			
52A	Upper bearing	6203ZZC3			
52B	Lower Bearing	6304ZZC3			
53	Motor Protector 380/400/415V-50Hz	KA314-HRXL00 (H.C)			